

Scientific Supervisor: Anthony Michel

Outline

- Context Problems and Challenges
- Linear Coupled Two Species System
- Nonlinear Coupled Two Species System
- Nonlinear Coupled Multispecies System
- Conclusion and Perspectives



CCS Carbon Capture and Storage

Technical process:



Physical and chemical phenomena:

- CO₂ dissolves partially in water and changes pH
- Acid water attacks rock matrix
- Change in geophysical properties has impact on Darcy flow





Physical challenges:

- Large domains and long simulation times
- Strong heterogeneity in time and space
- Occurring effects on different time scales
- Many chemical species (mobile and fixed)

Numerical challenges:

- Large coupled systems
- Strong nonlinearities



Existing Approaches for Reactive Transport

Splitting methods:

- + Highly developed solvers for subproblems
- Poor performance for long-term simulations with strong chemistry
- o local time-stepping for pure advective cases

Global Implicit Approach:

- + High-performing approaches for long-term simulation
- o Different formulations
- o local time-stepping not yet developed



Approach in this Work

Reactive Transport Model

- Global implicit approach
- Multispecies reactive transport
- Global-DAE formulation [Amir, Dieuleveult, Erhel, Kern] extended to kinetic reactions and mineral species

Domain Decomposition Approach

- Schwarz Waveform Relaxation (SWR)
- Localising heterogeneity affecting the performance of the non-linear solver
- Individual per subdomain time-stepping













SWR Schwarz Waveform Relaxation



Numerical Discretisation Using DD in the FV Context

- Implicit Euler method in time
- Hybrid Finite Volume scheme in space [Eymard, Gallouët, Herbin]



- Projection algorithm in space and time [Achdou, Japhet, Maday, Nataf], [Gander, Japhet]
- Numerical study of the influence of projections



Outline

- Context Problems and Challenges
- Linear Coupled Two Species System
- Nonlinear Coupled Two Species System
- Nonlinear Coupled Multispecies System
 - Conclusion and Perspectives



The Coupled System

$$\begin{aligned} \phi \partial_t u + \operatorname{div}(-a \vec{\nabla} u + \vec{b} u) - k(v - c u) &= 0 \quad \text{ on } \Omega \times (0, T) \\ \phi \partial_t v &+ k(v - c u) &= 0 \quad \text{ on } \Omega \times (0, T) \end{aligned}$$

- *u*: Mobile species
- v: Fixed species
- ϕ : Porosity
- a: Scalar diffusion coefficient
- \vec{b} : Darcy field
- k: Reaction rate coefficient
- c: Equilibrium constant



SWR Algorithm for the Coupled System



E SQA

$$\begin{split} \phi \partial_t u_1^{k+1} + \mathcal{L}(u_1^{k+1}) - k(v_1^{k+1} - cu_1^{k+1}) &= 0 & \text{on } \Omega_1 \times (0, T) \\ \phi \partial_t v_1^{k+1} & + k(v_1^{k+1} - cu_1^{k+1}) &= 0 & \text{on } \Omega_1 \times (0, T) \\ (u_1^{k+1}(x, 0), v_1^{k+1}(x, 0)) &= (u_0, v_0) & \text{on } \Omega_1 \\ \text{B. C.} & \text{on } \partial\Omega \cap \partial\Omega_1 \times (0, T) \\ \mathcal{B}_1 \left(u_1^{k+1}, v_1^{k+1} \right) &= \mathcal{B}_1 \left(u_2^k, v_2^k \right) & \text{on } \Gamma_1 \times (0, T) \end{split}$$

$$\begin{aligned} \phi \partial_t u_2^{k+1} + \mathcal{L}(u_2^{k+1}) - k(v_2^{k+1} - cu_2^{k+1}) &= 0 & \text{on } \Omega_2 \times (0, T) \\ \phi \partial_t v_2^{k+1} &+ k(v_2^{k+1} - cu_2^{k+1}) &= 0 & \text{on } \Omega_2 \times (0, T) \\ \text{B. C.} & \text{on } \partial\Omega \cap \partial\Omega_2 \times (0, T) \\ (u_2^{k+1}(x, 0), v_2^{k+1}(x, 0)) &= (u_0, v_0) & \text{on } \Omega_2 \\ \mathcal{B}_2 \left(u_2^{k+1}, v_2^{k+1} \right) &= \mathcal{B}_2 \left(u_1^k, v_1^k \right) & \text{on } \Gamma_2 \times (0, T) \end{aligned}$$

Evolution from Scalar Equation to Coupled System

Scalar equation:

 $\phi \partial_t u + \operatorname{div}(-a \vec{\nabla} u + \vec{b} u) \qquad -cu = 0 \quad \text{on } \Omega \times (0, T)$

Gander, Halpern, Kern: A SWR Method for Advection-Diffusion-Reaction Problems with Discontinuous Coefficients and non-Matching Grids. DD16, Springer, 2007. Bennequin, Gander, Halpern: A Homographic Best Approximation Problem with Application to Optimized SWR. Math. Comp. 78, no. 265, pp 185–223, 2009.

Coupled system:

$$\phi \partial_t u + \operatorname{div}(-a \vec{\nabla} u + \vec{b} u) - k(v - c u) = 0 \quad \text{on } \Omega \times (0, T) \\ \phi \partial_t v + k(v - c u) = 0 \quad \text{on } \Omega \times (0, T)$$



Well-posedness of the SWR Algorithm

- Well-posedness (energy estimates, Galerkin method)
 - Global problem
 - Sub-Problems using Robin/Ventcel conditions
 - SWR algorithm with different transmission conditions L ≥ 0

Theorem

Let p > 0 be given and L > 0. If $(u_0, v_0) \in H^2(\mathbb{R}^d) \times L^2(\mathbb{R}^d)$ and $g_{b_i^0} \in H^{\frac{1}{4}}(0, T; L^2(\Gamma_i)) \cap L^2(0, T; H^{\frac{1}{2}}(\Gamma_i))$, i = 1, 2, are given, then the SWR algorithm with the transmission operators defined by

 $\mathcal{B}_{1}(u,v) = \frac{\partial u}{\partial n_{1}} - \frac{b_{x} - p}{2a}u, \quad \mathcal{B}_{2}(u,v) = \frac{\partial u}{\partial n_{2}} + \frac{b_{x} + p}{2a}u,$ defines a unique sequence of iterates $((u_{1}^{k}, v_{1}^{k}), (u_{2}^{k}, v_{2}^{k}))$ such that $u_{i}^{k} \in L^{2}(0, T; H^{2}(\Omega_{i})) \cap H^{1}(0, T; L^{2}(\Omega_{i})), \quad v_{i}^{k} \in H^{1}(0, T; L^{2}(\Omega_{i})),$ for $i \in \{1, 2\}.$

Convergence of the SWR Algorithm



 Convergence and convergence factor of the SWR algorithm with different transmission conditions with/without overlap (energy estimates, Fourier transform)

Theorem

Let L > 0 and suppose that the advection speed b is such that $b_x \neq 0$. Let p > 0. Then the sequence $((u_1^k, v_1^k), (u_2^k, v_2^k))$ defined by the SWR algorithm with Robin transmission operators converges to $((u, v)_{|\Omega_1}, (u, v)_{|\Omega_2})$, in $\prod_{i=1}^2 (L^2(0, T; L^2(\Omega_i)) \times L^2(0, T; L^2(\Omega_i)))$ for $k \to \infty$.



Convergence of the SWR Algorithm



Optimised Transmission Conditions

- Numerical optimisation of parameters: Comparison between scalar adv.-diff. equation and coupled system
 - Parameters of scalar advection-diffusion equation applicable even for strong chemistry (Ventcel 1D; Robin and Ventcel in 2D, 3D)
 - Significant differences for Robin in 1D



Analytical Formula

 Analytical solution for Robin without overlap in 1D following [Bennequin, Gander, Halpern 2009]

$$p^* = \sqrt{2\mathfrak{Re}\left(\sqrt{b_x^2 + 4ad(\tau_m)}\right)\mathfrak{Re}\left(\sqrt{b_x^2 + 4ad(\tau_M)}\right)}, d(\tau) = \phi i\tau - \frac{k^2c}{\phi i\tau + k} + kc$$



Application of 1D Parameter in 2D/3D cases

Localised strategy in 2D/3D for advection-dominant cases:
 p = const ⇒ *p*(*x*) on Γ
 1D optimisation or Taylor approximation on every face



Outline

- Context Problems and Challenges
- Linear Coupled Two Species System
- Nonlinear Coupled Two Species System
- Nonlinear Coupled Multispecies System
- Conclusion and Perspectives





$$\begin{aligned} \phi \partial_t u + \operatorname{div}(-a \vec{\nabla} u + \vec{b} u) - R(u, v) &= 0 \quad \text{on } \Omega \times (0, T) \\ \phi \partial_t v &+ R(u, v) &= 0 \quad \text{on } \Omega \times (0, T) \end{aligned}$$

 $R: \mathbb{R}^2 \to \mathbb{R}$ nonlinear function



Optimised Transmission Conditions

Robin transmission condition

- Realisation as in the linear cases
- Accordance of optimised parameter with linear case



Mixing Newton and SWR

- 1. Classical approach:
 - Fixpoint (SWR (NLPb))
 - Nonlinear subproblems at every iteration
- 2. Nested Iteration Approach (NIA):
 - Newton-Krylov (SWR (NLPb))
 - Linearised problems for Jacobian evaluation
 - Nonlinear problems for residual evaluation
- 3. Common Iteration Approach (CIA):
 - Krylov-SWR (Newton (NLPb))
 - Linearised problems for Jacobian evaluation
 - Linearised problems for residual evaluation

[Haeberlein, Halpern, Michel, DD20, 2011, submitted]



- + Easy to add to standard approach
- + Accelerating properties



- + Easy to add to standard approach
- + Accelerating properties





- + Easy to add to standard approach
- + Accelerating properties





- + Easy to add to standard approach
- + Accelerating properties





Image: A matrix

- + Easy to add to standard approach
- + Accelerating properties
- o Needs adaptive strategy for linear solver to be performant
- Overhead cost for coarse discretisation \Longrightarrow No acceleration
- Storage cost for CIA
- Dependence of the performance on the character of the test case





- Advection-dominant cases
- Time-space localisation of chemical disequilibria
- Overlap
- Taylor approximation for Robin condition
- Initial state as guess for SWR
- \Rightarrow \approx 3 SWR iterations.
- Isolation of disequilibria in separate subdomain m(Ω_R) ≤ 0.3 m(Ω)
 Different time steps in subdomains 3Δt_R ≤ Δt_{NR}
 ⇒ ≈ 20 % gain in CPU time.



Outline

- Context Problems and Challenges
- Linear Coupled Two Species System
- Nonlinear Coupled Two Species System
- Nonlinear Coupled Multispecies System
- Conclusion and Pe



The Treated Problem Phases and Species





The Treated Problem Components Representation

Equilibrium reactions are represented by a Morel tableau:



Ideal activity model: $a_i = c_i$.

The Treated Problem The Chemical Flash



= 200

$$\begin{aligned} \theta_{w}c + \theta_{w}(S_{c}^{x})^{t}x + \theta_{s}(S_{c}^{y})^{t}y + (S_{c}^{z})^{t}(\theta_{z} \cdot z) &= T, \\ \theta_{s}s &+ \theta_{s}(S_{s}^{y})^{t}y &= W, \\ \theta_{q} \cdot q &= Q, \\ \ln(a_{x}) - (S_{c}^{x})\ln(a_{c}) &= \ln K_{x}, \\ \ln(a_{y}) - (S_{c}^{y})\ln(a_{c}) - (S_{s}^{y})\ln(a_{s}) &= \ln K_{y}, \\ \ln(a_{z}) - (S_{c}^{z})\ln(a_{c}) &= \ln K_{z}, \end{aligned}$$

$$\begin{aligned} \sum_{i=1}^{N_{c}} c_{i} + \sum_{i=1}^{N_{x}} x_{i} &= 1, \quad (\text{mobile phase}), \\ \sum_{i=1}^{N_{s}} s_{i} + \sum_{i=1}^{N_{y}} y_{i} &= 1, \quad (\text{sorbed phase, if present}), \\ q_{i} &= 1, \quad i = 1, \dots, N_{q}, \\ z_{i} &= 1, \quad i = 1, \dots, N_{z}. \end{aligned}$$

The Treated Problem Total Component RT Problem

$$\begin{split} \partial_t(\phi C) + \partial_t(\phi F) + \mathcal{L}(C) + R_{T,\text{kin}} &= 0 \qquad (\#C), \\ \partial_t W + R_{W,\text{kin}} &= 0 \qquad (\#W), \\ \partial_t Q + R_{Q,\text{kin}} &= 0 \qquad (\#Q), \end{split}$$

$$T - \phi C - \phi F = 0$$

oF - $\Psi(T, W, Q) = 0$

(#T), (#F),

 $R_{T,kin} - \Theta(T, W, Q) = 0$ $R_{W,kin} - \Upsilon(T, W, Q) = 0$ $R_{Q,kin} - \Xi(T, W, Q) = 0$

¢

 $(\#R_{T,kin}),$ $(\#R_{W,kin}),$ $(\#R_{Q,kin}).$



Numerical Approach for Reactive Transport Problem

- Adaptive time stepping strategy
- Hybrid finite volume scheme in space and implicit Euler in time discretisation
- Global Implicit Approach
- Solve complementary condition in algebraic equivalent version by semi-smooth Newton method [Hoffmann, Knabner, Kräutle]
 - prevent from negative concentrations for mineral species in global problem
 - manage disappearing mineral phases in local problem







image source: Princeton University

image sources: Thesis Th. Millan, IFP EN - Ecole des Mines de St Etienne





image sources: Thesis Th. Millan, IFP EN - Ecole des Mines de St Etienne



Mobile species: H₂O, tracer, CO₂(aq), CaO(aq), SiO₂(aq) Mineral species: Calcite, Wollastonite, Portlandite, Silica

Kinetic reactions:

- Portlandite Dissolution: Portlandite + CO₂(aq) → Calcite
- Wollastonite Dissolution: Wollastonite CaO(aq) + Silica CaO(aq) + Silica
- Calcite Precipitation: CaO(aq) + CO₂(aq) \longrightarrow Calcite
- Silica Dissolution: Silica $\xrightarrow{\text{CaO}(\text{aq})}$ SiO₂(aq)







Loading video...







Loading video...



ELE DOG

イロト イヨト イヨト イヨト

© IFP Energies nouvel

IFP Energies nouvelles and LAGA University Paris XIII - Time Space DD Methods for RT - 14 October 2011

42







-



Primary species:

$$c = \begin{pmatrix} c_1 \\ c_2 \\ c_3 \\ c_4 \\ c_5 \\ c_6 \\ c_7 \\ c_8 \end{pmatrix} = \begin{pmatrix} H_2 O \\ Tracer \\ CO_2(aq) \\ Cl^- \\ H^+ \\ Na^+ \\ Ca^{++} \\ SiO_2(aq) \end{pmatrix}, \qquad q = \begin{pmatrix} q_1 \\ q_2 \end{pmatrix} = \begin{pmatrix} Calcite \\ Quartz \end{pmatrix}$$

Secondary species:

$$x = \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{pmatrix} \text{HCO}_3^- \\ \text{OH}^- \end{pmatrix},$$

$$z = (z_1) = (\operatorname{CO}_2(\operatorname{solid}))$$

Image: A matrix





Equilibrium reactions:

- $\blacksquare H_2O \iff H^+ + OH^-$
- $\blacksquare CO_2(g) \iff CO_2(aq)$
- $\blacksquare H_2O + CO_2(aq) \iff HCO_3^- + H^+$

Kinetic reactions:

- **Calcite + H**⁺ \longleftrightarrow Ca⁺⁺ + HCO₃⁻
- $\blacksquare \text{ Quartz } \longleftrightarrow \text{ SiO}_2(\text{aq})$









Loading video...







Loading video...







Loading video...





Loading video...



Outline

- Context Problems and Challenges
- Linear Coupled Two Species System
- Nonlinear Coupled Two Species System
- Nonlinear Coupled Multispecies System
- Conclusion and Perspectives



SWR Domain Decom-

Conclusion:

- Application of previously developed theory and techniques to a coupled system
- Confirmation of results similar to scalar equations
 - Only optimised parameters offer fast convergence
 - Good accordance between theory and numerics

Perspectives:

- Optimised transmission conditions
 - for unknown temporal discretisation and
 - in the nonlinear case
- Comparative numerical tests for different proposed Ventcel conditions in the nonlinear case



A (10) × A (10) × A (10)



Conclusion:

- Two new numerical approaches developed
- Tested with success on nonlinear coupled system
 - Accelerating properties
 - Less sensibility to transmission condition parameter
 - Better asymptotic behaviour

Perspectives:

- More tests on other types of equations and other test cases
 - Investigation for eliminating overhead cost



Conclusion:

- Extension of existing formulation to kinetic reactions and minerals
- First approach of domain decomposition on nonlinear coupled multispecies reactive transport systems

Perspectives:

- Study of numerical formulation (stability, conditioning,...)
- Study of well-posedness of multispecies reactive transport formulation with given boundary data by domain decomposition algorithm



Limiting of Kinetic Reaction Rates

 $M \rightarrow A + B$, reaction rate k > 0

$$\frac{\mathbf{M}^{n+1} - \mathbf{M}^n}{\Delta t} + k = 0 \qquad \text{if } \mathbf{M}^{n+1} \ge 0$$
$$\mathbf{M}^{n+1} = 0 \qquad \text{else}$$

$$\frac{\mathbf{M}^{n+1}-\mathbf{M}^n}{\Delta t}+\min\left\{k,\frac{\mathbf{M}^n}{\Delta t}\right\}=0.$$



 $[\ln(a_z) - (S_c^z)\ln(a_c) - \ln K_z]_i = 0$ if mineral phase *i* is present $\theta_{z_i} = 0$ if mineral phase *i* is not present

 \uparrow

 $f := [\ln(a_z) - (S_c^z)\ln(a_c) - \ln K_z]_i$

$$arphi(f, heta_{Z_i})=f+ heta_{Z_i}-\sqrt{f^2+(heta_{Z_i})^2}=0$$

