On Models for Performance Analysis of a Core Cache Network and Power Save of a Wireless Access Network

Ph.D. Thesis defended by Nicaise E. CHOUNGMO FOFACK

Advisors: Philippe Nain and Sara Alouf





Outline

Introduction

Single cache

Cache networks under i.i.d. requests

Conclusion

Outline

Introduction Context In-network caching

Single cache

Cache networks under i.i.d. requests

Conclusion

Motivations

Focus

Power save protocols

• Reduce energy consumption

Motivations

Focus

Power save protocols

- Reduce energy consumption
- In-network caching
 - Reduce network traffic
 - Improve users QoE

Context

Problem 1: Power save protocols

Energy consumption problem (Statement)

- Study case: 3/4G cellular networks (LTE, WiMAX)
- Issue: Continous connectivity => Increase energy costs on TRX

Challenges:

- Discontinuous TRX protocols by 3GGP
- Realistic web traffic (non-Poisson)
- Both mobiles (UEs) and Node B (eNB)

Context

Problem 1: Power save protocols


Energy consumption problem (models)

- Performance metrics: Gains (UE & eNB), Delay, Power Ratio, Download time
- Qutcomes:
 - Optimal configuration of Discontinuous TRX protocols
 - Impact of inputs on the metrics of interest
 - Lessons: Up to 90% TRX costs, #UEs< 350, small web page, & small # embedded objects

S. Alouf, V. Mancuso, N. C. F., "Analysis of power saving and its impact on web traffic in cellular networks with continuous connectivity", Pervasive and Mobile Computing, 8(5):646-661, Oct. 2012

Benefits

- Reduce network traffic
- Improve Users QoE



Examples

• Domain Name System (worldwide, everyone uses it)

• CDNs and VoD Systems (Akamai, Google, Youtube, Orange)

• Content-Centric Network

(CCN, Xerox Parc, Jacobson et al.)

Issues

- 1 Design large scale cache networks
- 2 Models for performance evaluation cache nets
- **3** Optimization and control of "on-demand" caches (QoS, DiffServ)

Challenges & limitations of existing models

- Classical policies (LRU, FIFO, RND, etc.) not flexible enough
- No exact results even for Tandem of 2 caches
- Only approximations, limited by
 - Traffic models, IRM or Poisson processes
 - Topology and Routing, Tree-centric
 - Heterogeneity, Same policy everywhere
 - Accuracy and Complexity of performance models

Outline

Introduction

Single cache Cache architecture Practical concerns

Cache networks under i.i.d. requests

Conclusion

How does it work?

• On cache miss: add content, assign timer T to it

- On cache hit: two possibilities
 - ▶ Re-initialize timer 7
 - Use remaining value of 7

Remove content (only) when timer T expired

How does it work?


- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - ▶ Re-initialize timer 7
 - ▶ Use remaining value of *T*

Remove content (only) when timer T expired

How does it work?

- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - Re-initialize timer T
 - ▶ Use remaining value of T


▶ Remove content (only) when timer *T* expired



How does it work?


- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - Re-initialize timer T
 - ► Use remaining value of T

Remove content (only) when timer T expired



How does it work?

- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - Re-initialize timer T
 - Use remaining value of T
- Remove content (only) when timer T expired



How does it work?

- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - Re-initialize timer T
 - Use remaining value of T
- Remove content (only) when timer T expired

	LRU	RND	FIFO	TTL
Space	finite	finite	finite	Infinite
Time	unknown	unknown	unknown	Limited
Control	no way	no way	no way	yes, timers (rvs)

How does it work?

- On cache miss: add content, assign timer T to it
- On cache hit: two possibilities
 - Re-initialize timer T
 - Use remaining value of T
- Remove content (only) when timer T expired

TTL-based models are also interesting...

- extend easily to networks
- use to accurately describe LRU, RND, FIFO policies

Model

Assumptions

1. Cache size is INFINITE and ONLY TTLs are used

2. Delays are negligible




Figure: TTL decoupling effect \implies Focus on SINGLE CONTENT!

Model

Assumptions

- 1. Cache size is INFINITE and ONLY TTLs are used
- 2. Delays are negligible





Figure: TTL decoupling effect \implies Focus on SINGLE CONTENT!


Hit and Occupancy probs

▶ File requests form a stationary point process, $\{\mathcal{N}(t), t \ge 0\}$



Hit and Occupancy probs

▶ File requests form a stationary point process, $\{\mathcal{N}(t), t \ge 0\}$



Theorem (Stationary case)

$$H_{P} = r \mathbb{P}^{0} \left(X_{1} < T_{1} \right) + \bar{r} \left(1 - \left(1 + \mathbb{E}^{0} \left[\mathcal{N} \left(T_{1} \right) \right] \right)^{-1} \right)$$

$$O_{P} = \left(\mathbb{E}^{0} [X_{1}]^{-1} \times (1 - H_{P}) \right) \times \mathbb{E}^{0} [Q], \quad \text{`Mean-Value Formula''}$$
(2)

Q is the total sojourn time given by:

$$Q = \begin{cases} T_1 & \text{if } r = 0 \\ T_1 \times \mathbf{1}\{X_1 > T_1\} + (X_1 + \tilde{Q}) \times \mathbf{1}\{X_1 < T_1\} & \text{if } r = 1. \end{cases}$$

(3)

- Arrivals occur at jumps of a DTMC $\{\xi_i, i \ge 0\}$ on $S = \{1, 2, \dots, J\}$,
- ► Requests form a stationary Markov Renewal Process (MRP), $[\mathbf{F}(t)]_{j,k} := \mathbb{P}(X_i < t, \xi_{i+1} = j | \xi_i = k), \ T(t) = \mathbb{P}(T_1 < t)$

- Arrivals occur at jumps of a DTMC $\{\xi_i, i \ge 0\}$ on $S = \{1, 2, \dots, J\}$,
- ► Requests form a stationary Markov Renewal Process (MRP), $[\mathbf{F}(t)]_{j,k} := \mathbb{P}(X_i < t, \xi_{i+1} = j | \xi_i = k), \ T(t) = \mathbb{P}(T_1 < t)$

Proposition (Kernel of the miss process)

Miss process is a MRP, with kernel

$$\mathbf{G}^{(0)}(t) = \mathbf{F}(t) - \int_0^t \mathrm{d}\mathbf{R}(x)(\mathbf{I} - \mathbf{F}(t - x))$$
(4)

$$\mathbf{G}^{(1)}(t) = \mathbf{F}(t) - \mathbf{L}(t) + \int_0^t \mathrm{d}\mathbf{L}(x)\mathbf{G}^{(1)}(t-x)$$
(5)

$$[\mathbf{L}(t)]_{j,k} := \int_0^t (1 - T(x)) \mathrm{d}F_{j,k}(x), \ [\mathbf{R}(t)]_{j,k} := \int_0^t (1 - T(x)) \mathrm{d}M_{j,k}(x)$$

•
$$S = \{1\} \implies \text{Renewal process}, F(t) = \mathbb{P}(X_1 < t), M(t) = \mathbb{E}[\mathcal{N}(t)]$$

Corollary (CDF of the inter-miss times)
Miss process is a renewal process, and
$$\mathbb{P}(Y < t)$$

$$G^{(0)}(t) = F(t) - \int_0^t (1 - T(x)) dM(x) (1 - F(t - x))$$

$$G^{(1)}(t) = F(t) - \int_0^t (1 - T(x)) dF(x) + \int_0^t (1 - T(x)) dF(x) G^{(1)}(t - x)$$

Hint, $\mathcal{S} = \{1\}.$

▶
$$S = \{1\} \implies \text{Renewal process}, F(t) = \mathbb{P}(X_1 < t), M(t) = \mathbb{E}[\mathcal{N}(t)]$$

Corollary (CDF of the inter-miss times) Miss process is a renewal process, and $\mathbb{P}(Y < t)$ $G^{(0)}(t) = F(t) - \int_0^t (1 - T(x)) dM(x) (1 - F(t - x))$ $G^{(1)}(t) = F(t) - \int_0^t (1 - T(x)) dF(x) + \int_0^t (1 - T(x)) dF(x) G^{(1)}(t - x)$

Hint, $\mathcal{S} = \{1\}$.

$$Y = \begin{cases} X_1 + \dots + X_{\mathcal{N}(T_1)+1} & \text{if } r = 0 \\ X_1 \ \mathbf{1}(X_1 > T_1) + (X_1 + \tilde{Y}) \ \mathbf{1}(X_1 < T_1) & \text{if } r = 1. \end{cases}$$

How to set up a TTL-based model?

Proposition (Optimal TTL distribution)

If F(t) is concave then Deterministic TTL performs the best.

How to set up a TTL-based model?

Proposition (Optimal TTL distribution)

If F(t) is concave then Deterministic TTL performs the best.

Hint.

- Consider T and D s.t. $\mathbb{E}[T] = D$
- show $D <_{CX} T$ (Jensen's Inequality)
- Express $H_P = \mathbb{E}[f(T)]$ and $O_P = \mathbb{E}[g(T)]$, f concave, g cvx

How to set up a TTL-based model?

Proposition (Optimal TTL distribution)

If F(t) is concave then Deterministic TTL performs the best.

Hint.

- Consider T and D s.t. $\mathbb{E}[T] = D$
- show $D <_{CX} T$ (Jensen's Inequality)
- Express $H_P = \mathbb{E}[f(T)]$ and $O_P = \mathbb{E}[g(T)]$, f concave, g cvx

Remark (Conjecture... from experiments)


Otherwise, TTL distr. with strictly positive c_v^2 (e.g. hypo/exp/hyper).

Validation with real data: traces from Inria DNS cache

- ▶ TTL-non-renewing cache, 6-th most popular content, TTL T = 2h
- Match higher order and joint moments using Markov Arrival Process
- Use analytic CDF F(t) as input of TTL model


Validation with real data: traces from Inria DNS cache

- ▶ TTL-non-renewing cache, 6-th most popular content, TTL T = 2h
- Match higher order and joint moments using Markov Arrival Process
- Use analytic CDF F(t) as input of TTL model
- Inter-requests are correlated & good approximation of G(t)




Validation with real data: traces from Inria DNS cache

- TTL-non-renewing cache, 6-th most popular content, TTL T = 2h
- Match higher order and joint moments using Markov Arrival Process
- Use analytic CDF F(t) as input of TTL model
- Inter-requests are correlated & good approximation of G(t)



(i) ACF inter-arrival times



(j) CDF inter-miss times

Performance metrics: accurate predictions

Metric	Trace	Model	Rel. err. (%)
miss rate	0.00013876	0.00013749	0.920
hit prob.	0.99943	0.99941	0.002
occupancy	0.99914	0.98995	0.920

Accounting for constraints: Practical (Pra)-TTL

Pra-TTL: Deployment of TTL model

- Cache miss: add content and assign TTL
- ▶ Timer expiration: keep it in cache
- Buffer full: drop content that expired (or will expire sooner)

How to calculate TTLs? ...subject to constraints

Accounting for constraints: Practical (Pra)-TTL

Pra-TTL: Deployment of TTL model

- Cache miss: add content and assign TTL
- ▶ Timer expiration: keep it in cache
- Buffer full: drop content that expired (or will expire sooner)

How to calculate TTLs? ...subject to constraints

- Energy / Holding costs: $\sum_{f} (1 H_{P,f})c_{t,f} + O_{P,f}c_{h,f} \leq \delta$
- ▶ Refresh rate: $M_{R,f} \ge \eta$, (e.g. DNS cache)
- Capacity: $\sum_{f} O_{P,f} = B$, (e.g. Web cache)

Practical concerns

TTL model prediction versus Pra-TTL simulation results

- Linear network of 5 Exp. TTL-based caches
- Constraint: Cache size B = 20
- Experiment: Poisson ($\lambda_1 = 2$), Zipf($\alpha = 1.2$), Catalog size N = 200





Figure: Cache 5 (root node)

TTL models and LRU, FIFO, RND

- Cache of size B, Content n requested ONLY ONCE, time spent $T_{B,n}$
- Experiment: Poisson ($\lambda = 1$), Zipf($\alpha = 0.65$), $B = 10^2$, Catalog size $N = 10^4$



Outline

Introduction

Single cache

Cache networks under i.i.d. requests Hierarchial networks: Tree/Polytree General cache networks

Conclusion

Nets

Nets (Poly)Tree

Step by step analysis (I)

Multiple sources

Merging renewal request streams, CDF of first inter-request time




Figure: Exact results on Linear-star networks

Multiple sources

Merging renewal request streams, CDF of first inter-request time

1. Lawrence's Theorem
$$\implies$$
 Exact CDF
 $1 - A(t) = \sum_{k=1}^{K} \frac{\lambda_k}{\sum_{l=1}^{K} \lambda_l} (1 - A_k(t)) \prod_{i=1, i \neq k}^{K} \lambda_j \int_t^{\infty} (1 - A_j(u)) du$ (4)

Multiple sources

Merging renewal request streams, CDF of first inter-request time

1. Lawrence's Theorem
$$\implies$$
 Exact CDF
 $1 - A(t) = \sum_{k=1}^{K} \frac{\lambda_k}{\sum_{l=1}^{K} \lambda_l} (1 - A_k(t)) \prod_{j=1, j \neq k}^{K} \lambda_j \int_t^{\infty} (1 - A_j(u)) du$ (4)

2. Poisson approx. \implies Exponential CDF

$$A(t) = 1 - e^{-\Lambda t}, \qquad \Lambda = \sum_{l=1}^{K} \lambda_l, \quad c_p^2 = 1$$
 (5)

Multiple sources

Merging renewal request streams, CDF of first inter-request time

1. Lawrence's Theorem
$$\implies$$
 Exact CDF

$$1 - A(t) = \sum_{k=1}^{K} \frac{\lambda_k}{\sum_{l=1}^{K} \lambda_l} (1 - A_k(t)) \prod_{j=1, j \neq k}^{K} \lambda_j \int_t^{\infty} (1 - A_j(u)) \, \mathrm{d}u \qquad (4)$$

2. Poisson approx.
$$\implies$$
 Exponential CDF

$$A(t) = 1 - e^{-\Lambda t}, \qquad \Lambda = \sum_{l=1}^{K} \lambda_{l}, \quad c_{\rho}^{2} = 1$$
(5)

- 3. Whitt approx. \implies 2-state Hyper-exp. / Shifted-exp. CDFs
 - asymptotic method, Λ and c_a^2 , moments of $\frac{\mathcal{N}(t)}{t}$
 - stationary interval, Λ and c_s^2 , moments of X_1

Multiple sources

Merging renewal request streams, CDF of first inter-request time

1. Lawrence's Theorem
$$\implies$$
 Exact CDF

$$1 - A(t) = \sum_{k=1}^{K} \frac{\lambda_k}{\sum_{l=1}^{K} \lambda_l} (1 - A_k(t)) \prod_{j=1, j \neq k}^{K} \lambda_j \int_t^{\infty} (1 - A_j(u)) \, \mathrm{d}u \qquad (4)$$

2. Poisson approx.
$$\implies$$
 Exponential CDF

$$A(t) = 1 - e^{-\Lambda t}, \qquad \Lambda = \sum_{l=1}^{K} \lambda_{l}, \quad c_{\rho}^{2} = 1$$
(5)

- 3. Whitt approx. \implies 2-state Hyper-exp. / Shifted-exp. CDFs
 - asymptotic method, Λ and c_a^2 , moments of $\frac{\mathcal{N}(t)}{t}$
 - stationary interval, Λ and c_s^2 , moments of X_1
- 4. Hybrid Approx. $\implies \Lambda$ and $c_h^2 = wc_s^2 + (1 w)c_p^2$
 - combines Poisson and Whitt (stationary interv) approx.
 - provides empirical expressions of w

Multiple destinations

Splitting a request stream (e.g. Bernoulli routing with prob. p)




Figure: Polytree network

Multiple destinations

Splitting a request stream (e.g. Bernoulli routing with prob. p)


- 1. Sum of geometric number of i.i.d. $X_i \Longrightarrow$ Exact result
- 2. Poisson, Whitt, and Hybrid approx. (moments matching)

$$E[X_{i,th}] = \frac{E[X_i]}{p}$$
$$E[X_{i,th}^2] = \frac{E[X_i^2]}{p} + 2\frac{1-p}{p^2}(E[X_i])^2$$

(Poly)Tree

Heterogeneous (LRU, RND, or FIFO) tree cache networks

- 4-ary tree of depth 5 with 341 caches (LRU, RND, or FIFO)
- Experiment: Poisson requests at leaves ($\lambda = 1$), Zipf($\alpha = 0.7$), $B \in [50, 150]$, $N = 10^4$



(Poly)Tree

Heterogeneous (LRU, RND, or FIFO) tree cache networks

- 4-ary tree of depth 5 with 341 caches (LRU, RND, or FIFO)
- Experiment: Poisson requests at leaves ($\lambda = 1$), Zipf($\alpha = 0.7$), $B \in [50, 150]$, $N = 10^4$





Figure: Hybrid approximation


Heterogeneous (LRU, RND, or FIFO) tree cache networks

- 4-ary tree of depth 5 with 341 caches (LRU, RND, or FIFO)
- Experiment: Poisson requests at leaves ($\lambda = 1$), Zipf($\alpha = 0.7$), $B \in [50, 150]$, $N = 10^4$




Routing topology and State dependencies

Consider this five caches network



Iterative procedure for our 5 caches network


- LRU policy at all caches, Two classes of contents (k = [1..500], [501..1000])
- Experiment: per-class Poisson requests ($\lambda = 1$), Zipf($\alpha = 0.7$), $B = 10^2$, $N = 10^3$



Cache 3, Policy:LRU, Capacity: 100

Iterative procedure for our 5 caches network

- LRU policy at all caches, Two classes of contents (k = [1..500], [501..1000])
- Experiment: per-class Poisson requests ($\lambda = 1$), Zipf($\alpha = 0.7$), $B = 10^2$, $N = 10^3$



Outline

Introduction

Single cache

Cache networks under i.i.d. requests

Conclusion

Take off message

- Cache networks
 - Think "TTL model"
 - Apply your constraints (capacity, delay, energy, bandwidth,...)
 - Deploy your "TTL model" using LRU, RND, FIFO or Pra-TTL
- New research opportunities
 - Non-zero delays
 - q-LRU and LFU policies
 - Temporal and geographical locality problems
 - QoS and cache optimization problems
- TTL-based behaviors not only in cache networks
 - Economics: Product warranty
 - Physics: Geiger-Müller counters (of particles)
 - Smart device design (idle mode)

Take off message

- Cache networks
 - Think "TTL model"
 - Apply your constraints (capacity, delay, energy, bandwidth,...)
 - Deploy your "TTL model" using LRU, RND, FIFO or Pra-TTL
- New research opportunities
 - Non-zero delays
 - q-LRU and LFU policies
 - Temporal and geographical locality problems
 - QoS and cache optimization problems
- TTL-based behaviors not only in cache networks
 - Economics: Product warranty
 - Physics: Geiger-Müller counters (of particles)
 - Smart device design (idle mode)

List of publications

[1] S. Alouf, V. Mancuso, N. Choungmo Fofack,

"Analysis of power saving and its impact on web traffic in cellular networks with continuous connectivity", *PMC*, vol. 8, no. 5, pp. 646-661, 2012.

- [2] N. Choungmo Fofack, P. Nain, G. Neglia and D. Towsley, "Analysis of TTL-based cache networks", in Proc. ValueTools, Oct. 2012.
- [3] N. Choungmo Fofack and Sara Alouf, "Modeling modern DNS caches", in Proc. ValueTools, Dec. 2013.
- [R] N. Choungmo Fofack, P. Nain, G. Neglia and D. Towsley, "Performance analysis of hierarchical TTL-based cache networks", under minor revisions at Computer Networks.
- [S] N. Choungmo Fofack, M. Dehghan, D. Goeckel and D. Towsley, "An approximate analysis of general and heterogeneous cache networks", to be submitted to Performance, Mar. 2014.